

WIDE BODY LED EXIT LIGHT







Replaceable decals for single or double-sided mounting

Features:

- Fits most existing wide body exit bracket for quick light replacement – saves time & minimizes ceiling damage
- Long life Lithium Ion Battery
- **≠** 50,000 hr LED Energy efficient, long life
- Quick fit bracket for fast ceiling or wall mounting
- Easy testing & maintenance
- Premium range Industry leading photometric classification





AS/NZS: 60598.2.22 AS/NZS:60598.1

Specifications:

Voltage (V)	Battery Capacity	Frequency (Hz)	Charging Time	Duration	Max. Ambient Temp.	Power Consumption	
220 - 240	1500mAh	50/60	16 Hours	2 Hours	50°C	3 Watts	
Battery Type	Battery Voltage (V)	Viewing Distance	Mode	Mounting Type	IP Rating		
Li-lon	3.2	24m	Maintained	Wall or Ceiling	IP20		

Classification	Wall Mounted	Ceiling Mounted	Emergency Mode		
CO	D8	D12.5	D16		
C90	D5	D12.5	D16		

Spacing Table & Mounting Height:

oparing ravio a mounting respire												
(m)	2.1	2.4	2.7	3.0	3.3	3.6	4.0	4.5	5.0	6.0	7.0	8.0
D5	7.8	8.0	8.1	8.2	8.2	8.2	8.0	7.7	7.3	5.7	1.6	
D8	9.4	9.7	9.9	10.1	10.2	10.3	10.4	10.3	10.2	9.5	8.3	6.1
D12.5	11.1	11.5	11.8	12.1	12.4	12.5	12.7	12.9	13.0	12.8	12.3	11.3
D16	12.1	12.6	13.0	13.3	13.6	13.9	14.1	14.6	14.6	14.6	14.4	13.8

Based on minimum light level of level of 0.2 lux

