

## **FIRE HOSE RE**




Wolf Hose Reel Techinical Data Sheet



- Stainless Steel Waterway • Full Center Drum Spindle Stainless Steel Bolts
  - Heavy Duty Connection Block
  - Test By 2,000 kPa Hydraulic Pressure
  - Easy Installation

Woll Hose neel lechilileal Data Sheet	
Item No.	HR36-GREEN /HR36-BLUE
BSI Certificate No.	544723
Activfire Certificate No.	AFP-2355
Design Manufacture Standard	AS1221
Side Plate	Material: 1.0mm Mild Steel Diameter: 460mm Finishing: Powder Coating Color: Red
Hose Support	Material: 1.0mm Mild Steel Diameter: 180mm x 200mm Finishing: Powder Coating Color: Red
Mark Plate	Material: 1.0mm Mild Steel Diameter: 216mm Finishing: Powder Coating Color: Red
Inlet Pipe	1" Galvanized Steel
Waterway	Stainless Steel
PVC Hose with AS/NZ 1221 Certificate	3/4" x 36m Color: Black
Hose Reel Shut-off Valve with Watermark certificate	Spec. No. 12 LIC WMK50016
Brass Nozzle	Jet
Workin Pressure/Test Pressure	12 Bar / 20 Bar
Package Size	510 x 280 x 510



A warranty of twelve (12) months from the date purchase applies to all Wolf fire hose reels when installed to Australian standards AS 2441:2005 and serviced and maintained in accordance to AS 1851:2005

Wolf fire hose reels have been designed and manufactured according to AS/NZ 1221:1997. All Wolf fire hose reels carry the BSI Benchmark and Activefire certification. Ball valve has been certified with WaterMark No. W50016.







